	paint on metal stays, framing, etc								
2.	Security fencing 1800mm high vertically with 600mm long 45 grade to one side formed of 50mm diameter standards 2500mm long with 600mm overhang cast into and including 300x300x750mm 20MPa concrete base at average 3m centres, four rows of galvanised straining wires and four rows of 2.5mm galvanised double strand reverse twist barbed wire tied to standards, posts and eye bolts, the 1800mm vertical height covered with 50mm galvanised diamond wire mesh fixed at 300mm centres to each straining wire.	256.00	m						
3.	50mm Diameter inclined stay or vertical post 3m long with one end bent to detail and bolted to post and the other end with sole plate cast in and including 20MPa concrete base size 600x600x600mm	81.00	no						
4.	110mm corner or straining posts 2.7m high vertically with 600mm long 45 grade overhang with capped end and other end with sole plate cast in and including 20MPa concrete base size 450x450x600mm deep	10.00	no						
	Gates in Security fencing								
5.	Gate size 1000x1800mm high overall with 600mm long 45 grade overhang with barbed wire and covered with 50mm galvanized diamond wire mesh as for fencing and with suitable eye-bolt hinges and 300mm long galvanized drop bolts fixed in position complete	1.00	no						
	Sub-total for construction cost:								
	Preliminaries 8%:								
	VAT (15%):								
	Grand Total								